Precision Test Adapters

2.92 mm(M) to 2.92 mm(M)

Microwave Farm's Precision Test Adapters are designed based on precision microwave interconnection technologies.
This 2.92 mm(M) to 2.92 mm(M) adapter is manufactured to precise microwave specifications and constructed with male gender on side 1 and male gender side 2.
The precision microwave connector interfaces ensure an excellent microwave performance up to 40 GHz

■ *Features*

- Frequency range : DC to 40 GHz
- VSWR : 1.20 : 1(Max) @ 40 GHz
- Stainless steel (passivated)

■ *Specification*

Scope	Specification	AD03M03MS1
Electrical	Impedance(Ohm)	50
	Operation Freq.(GHz)	DC to 40 GHz
	VSWR (Max)	1.20 : 1
Material	Dielectric	Special dielectric
	Center Contact	Beryllium copper with gold plated
	Body	Passivated Stainless Steel

** RoHS Compliant*

info@takitek.com
www.takitek.co.jp

Precision Test Adapters

2.92 mm(M) to 2.92 mm(M)

■ *Drawing*

Part No.: AD03M03MS1

Unit : mm



■ *Test Result*

- **Frequency : 10 MHz to 40 GHz**

info@takitek.com
www.takitek.co.jp